

qbunlock

[[Description](#)] [[Usage](#)] [[Options](#)] [[Notes](#)] [[Examples](#)] [[See also](#)]

Description

Unlocks the available job slots on a Worker.

Usage

qbunlock [*options*] *hostname*...

where *hostname* is the name of the host to be unlocked. It can be followed by 0 or more *hostnames*.

Options

Switch	Description
--all	Unlock all hosts
--down	Unlock down hosts
--panic	Unlock panicked hosts
--active	Unlock active hosts
--cluster <i>string</i>	Unlock hosts in <i>string</i> cluster
--group <i>string</i>	Unlock hosts in <i>string</i> group
--resources <i>string</i>	Unlock hosts based upon requirements expression <i>string</i>
--purge	Immediately stop job processes running on Worker
--lock	Lock the Worker (deprecated: use qblock)
--unlock	Unlock the Worker (deprecated and implied)
--range <i>string</i>	Range <i>string</i> of CPU slots to lock/unlock. (deprecated: use qblock)
--value	Specify custom lock
--file <i>string</i>	Use the lock in the specified <i>string</i> file
--help	Command help
--version	Command version

Notes

Examples

Unlocks all slots on host render01

```
% qbunlock --lock render01
```

See also

[qblock](#)

