

# Telling the Supervisor to Reread the qb.conf file

The Supervisor may be told to reread the qb.conf file, without restarting the Supervisor service/daemon, to refresh certain dynamically modifiable parameters, by using the [qbadmin](#) command as in:

```
% qbadmin supervisor --reread
```

The following qb.conf supervisor parameters are dynamically modifiable:

- qb\_domain
- supervisor\_default\_group\_security
- supervisor\_default\_hostorder
- supervisor\_default\_max\_cpus
- supervisor\_default\_p\_agenda\_priority
- supervisor\_default\_pgrp\_subjob\_limit
- supervisor\_default\_priority
- supervisor\_default\_user\_subjob\_limit
- supervisor\_flags
- supervisor\_global\_resources
- supervisor\_highest\_user\_priority
- supervisor\_job\_flags
- supervisor\_max\_cpus\_limit
- supervisor\_max\_metered\_licenses
- supervisor\_max\_priority
- supervisor\_p\_agenda\_max
- supervisor\_pgrp\_subjob\_limits
- supervisor\_preempt\_policy
- supervisor\_smart\_share\_mode
- supervisor\_smart\_share\_preempt\_policy
- supervisor\_user\_subjob\_limits
- supervisor\_verbosity
- supervisor\_worker\_configfile